

Method of providing a metal pattern on glass in an electroless process.

Patent Number: EP0577187

Publication date: 1994-01-05

Inventor(s): WILLARD NICOLAAS PETRUS (NL); CAMPS IVO GODFRIED JOZEF (NL); FOKKINK LAMBERTUS GERRIT JAN (NL); VAN DER PUTTEN ANDREAS M T P (NL)

Applicant(s): PHILIPS ELECTRONICS NV (NL)

Requested Patent: ☐ EP0577187, B1

Application Number: EP19930201804 19930622

Priority Number(s): EP19930201804 19930622; EP19920201925 19920629

IPC Classification: C03C17/38; G03F7/075

EC Classification: C03C17/38, G02F1/1335F1, G03F7/075F

Equivalents:

Cited Documents: JP61199071

Abstract

Metal patterns (15) can be provided on a glass substrate (1) in an electroless process by modifying the substrate with a silane layer (3), locally removing said layer with a laser or UV-ozone treatment and selectively nucleating the remaining silane layer in a polymer-stabilized Pd sol. Neither a photoresist nor organic solvents are used. The method is very suitable for the manufacture of the black matrix on a passive

plate for a LCD, or on panels of other flat colour displays, such as flat cathode ray tubes.



Data supplied from the esp@cenet database - I2